

Unique identification code of the product:

MARMOLINE SVR (1 - 1.5 - 2 - 3 mm)

Render based in organic binders.

It refers to all batches of MARMOLINE SVR, produced after the issue of the present declaration

Intended use /es:

Finish coat dispersion plaster. Basic use: application on thermal insulation boards, on “MARMOLINE MONOSIS” ETICS or other similar ETICS systems

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

Manufacturing plant: 1st klm Country road Markopoulou-Oropou, 19014 Polydendri Attikis/ Greece

Systems of AVCP: System 3

Harmonized standard: EN 15824:2017

Notified Body: 0800, 1391

Declared performance /s:

| Essential characteristics | Performance | Technical spec. |
|---------------------------|--|--------------------------------------|
| Water vapour permeability | V1 (high) | EN 15824:2009 § 4.2 EN ISO 7783-2 |
| Water absorption: | W3 (low) | EN 15824:2009 § 4.3 EN 1062-3 |
| Adhesion: | ≥ 0.80 MPa | EN 15824:2009 § 4.4 EN 1542 |
| Thermal conductivity: | SVR 1 & 1.5 mm: $\lambda_{10,dry} = 0.83$ W/mK SVR 2 & 3mm: $\lambda_{10,dry} = 1.17$ W/mK (tab. mean value; P= 50%) | EN 15824:2009 § 4.6 EN 1745 |
| Reaction to fire: | A2-s2, d0 | EN 15824:2009 § 4.7 EN 13501-1 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Chalandri, 17/6/2020

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211319
364 KIFISSIAS AVENUE
CHALANDRI - 15233 - ATHENS GR
TEL. 0030 - 210 - 68 96 480
FAX. 0030 - 210 - 68 53 410

Andreas Alt
General Manager – NORDIA S.A.